

QC  
Avro  
CF105  
72-FAR-14  
Iss. 3

37

ARROW 2

72/FAR/14  
Issue 3

STANDARD INSTRUMENTATION  
AIRCRAFT 25210 THROUGH 25220

Oct. 1958



Inter-Departmental Memorandum

Ref 5323/01/J  
Date October 29, 1958  
To Mr. S.E. Harper  
From T. Roberts  
Subject ARROW INSTRUMENTATION - 72/FAR/14

Delete

The telemetry requirements of 72/FAR/14, issue 3, sheet 1, for aircraft 25210 to 25220 inclusive. These aircraft will have oscillograph recording only.

/b

T. Roberts  
Technical Design Coordinator  
FLIGHT TEST

PROJECT APPROVAL

C.C.  
Messrs J. Chamberlin  
F. Brame  
D. Scard  
D. Woolley (6)  
A. Buley  
J. Hodge  
J. Ames  
F. Mitchell  
J. Scott  
S. Kwiatkowski  
T. Higgins  
C. Marshall  
S. Brown  
G. Shaw  
J. Housego  
A. Matheson  
J. Gale

S. Whiteley  
D. Ridler  
R. Young  
J. Clark

Central Files

NRC - CISTI  
AERO / M.E.  
LIBRARY

89- 05- 12

BIBLIOTHÈQUE  
AÉRO / G.M.  
CNRC - ICIST



Inter-Departmental Memorandum

Ref 4927/02A/J  
Date October 17, 1958  
To Mr. S. E. Harper  
From T. Roberts  
Subject ARROW 2 - STANDARD INSTRUMENTATION

Report No. 72/FAR/14, Issue 3, covering standard instrumentation to be installed in aircraft 25210 through 25220, is attached.

A handwritten signature in cursive script, appearing to read "T. Roberts".

T. Roberts  
Technical Design Coordinator  
FLIGHT TEST

A handwritten signature in cursive script, appearing to read "A. Bulley".

Project Approval



AVRO AIRCRAFT LIMITED

MALTON - ONTARIO

TECHNICAL DEPARTMENT (Aircraft)

AIRCRAFT: Arrow 2

REPORT NO: 72/FAR/14 Issue 3

FILE NO:

NO. OF SHEETS: 7

TITLE:

ARROW 2

STANDARD INSTRUMENTATION

AIRCRAFT 25210 THROUGH 25220

PREPARED BY W.C. Etherington DATE October/58

CHECKED BY *T Roberts* DATE

SUPERVISED BY DATE

APPROVED BY DATE

ISSUE NO.	REVISION NO.	REVISED BY	APPROVED BY	DATE	REMARKS



CIRCULATION

J. Chamberlin  
F. Brame  
D. Scard  
D. Woolley (6)  
A. Buley  
J. Hodge  
J. Ames  
F. Mitchell  
J. Scott  
S. Kwitakowski  
T. Higgins  
C. Marshall  
S. Brown  
G. Shaw  
J. Housego  
A. Matheson  
J. Gale  
S. Whiteley  
D. Ridler  
R. Young  
J. Clark

STANDARD INSTRUMENTATION - ARROW 2

This report is issued to cover standard instrumentation requirements for aircraft 25210 through 25220.. Oscillograph recording will be utilized, and telemetry will be installed to cover the measurements listed in IDM 4547/01/J.

Wiring provision and any transducers inaccessible after build should be installed. The parameters to be recorded on a particular flight will be specified in the appropriate R.F.T.'s.



STANDARD INSTRUMENTATION - ARROW 2

INDEX

1. Telemetry
2. Stability and Control
3. Electrics
4. Air Conditioning
5. Cameras (provision for)

STANDARD INSTRUMENTATION - ARROW 2Section 1 - Telemetry

The following accident investigation parameters are to be telemetered:

- Altitude
- Indicated Airspeed
- Normal Acceleration
- Lateral Acceleration
- Elevator Angle
- Aileron Angle
- Rudder Angle
- Roll Rate
- Pitch Rate
- Yaw Rate
- Damper Configuration

STANDARD INSTRUMENTATION - ARROW 2Section 2 - Stability and Control1. Ambient Conditions

ITEM	RANGE	ACCURACY	ACCURACY % OF FULL RANGE
Aircraft Static Pressure	0 to 2160	$\pm 15$	$\pm 0.75\%$
Limited Range	0 to 720	$\pm 5$	$\pm 0.75\%$
Limited Range	0 to 288	$\pm 2$	$\pm 0.75\%$
Differential Pressure	0 to 2880	$\pm 20$	$\pm 0.75\%$
Limited Range	0 to 1440	$\pm 10$	$\pm 0.75\%$
Limited Range	0 to 720	$\pm 5$	$\pm 0.75\%$
Free Air Total Temperature	-65 to +350°F	$\pm 2^\circ\text{F}$	$\pm 0.5\%$

2. Motion of Aircraft

Angle of Pitch $\Theta$	-60° to +60°	$\pm 0.6^\circ$	$\pm 0.5\%$
Angle of Bank $\phi$	-85° to +85°	$\pm 0.8^\circ$	$\pm 0.5\%$
Angle of Sideslip $\beta$	-15° to +15°	$\pm 0.1^\circ$	$\pm 0.5\%$
Angle of Attack $\alpha$	-6° to +30°	$\pm 0.1^\circ$	$\pm 0.3\%$
Lateral Acceleration $\ddot{Y}$	-1 to +1g	$\pm 0.01g$	$\pm 0.5\%$
Normal Acceleration $\ddot{Z}$	-3 to +8g	$\pm 0.06g$	$\pm 0.5\%$
Longitudinal Acceleration $\ddot{X}$	-1 to +1g	$\pm 0.01g$	$\pm 0.5\%$
Rate of Pitch $\dot{\Theta}$	-30 to +30°/sec	$\pm 0.3^\circ/\text{sec}$	$\pm 0.5\%$
Heading Reference	0 to 360°	$\pm 3^\circ$	

STANDARD INSTRUMENTATION - ARROW 2Section 3 - Electrics

ITEM	RANGE	ACCURACY	ACCURACY % OF FULL RANGE
Voltage A $\emptyset$ left alternator	0 to 130V AC	$\pm 0.75V$	$\pm 0.5\%$
Voltage B $\emptyset$ left alternator	0 to 130V AC	$\pm 0.75V$	$\pm 0.5\%$
Voltage C $\emptyset$ left alternator	0 to 130V AC	$\pm 0.75V$	$\pm 0.5\%$
Current A $\emptyset$ left Alternator	0 to 120 A	$\pm 0.6 A$	$\pm 0.5\%$
Current B $\emptyset$ left alternator	0 to 120 A	$\pm 0.6 A$	$\pm 0.5\%$
Current C $\emptyset$ left alternator	0 to 120 A	$\pm 0.6 A$	$\pm 0.5\%$
Frequency left alternator (any one phase)	350 to 450 cps	$\pm 1 cps$	$\pm 1\%$

STANDARD INSTRUMENTATION - ARROW 2Section 4 - Air Conditioning(a) Static Pressure (psia):

ITEM	RANGE	ACCURACY	ACCURACY % OF FULL RANGE
Out of Turbine	0 to 20	$\pm 0.4$	$\pm 2\%$
Into Armament Bay	0 to 20	$\pm 0.4$	$\pm 2\%$
Into Nose Radar	0 to 20	$\pm 0.4$	$\pm 2\%$
Inside Nose Wheel Well	0 to 20	$\pm 0.4$	$\pm 2\%$
Into Oxygen Converter	0 to 20	$\pm 0.4$	$\pm 2\%$
Into Dorsal Radar	0 to 20	$\pm 0.4$	$\pm 2\%$
Into Transformer Rectifier Unit	0 to 20	$\pm 0.4$	$\pm 2\%$

(b) Temperature (°F)

Into Cockpit	0 to 300	$\pm 6$	$\pm 2\%$
Into Armament Bay	32 to 140	$\pm 2$	$\pm 2\%$
Into Nosewheel Well	50 to 200	$\pm 3$	$\pm 2\%$
Into Nose Radar	40 to 120	$\pm 1.6$	$\pm 2\%$
Into Transformer Rectifier Unit	40 to 120	$\pm 1.6$	$\pm 2\%$
Into Dorsal Radar	40 to 120	$\pm 1.6$	$\pm 2\%$
Out of Dorsal Radar	50 to 200	$\pm 3$	$\pm 2\%$



STANDARD INSTRUMENTATION - ARROW 2

Section 5 - Cameras

Wiring and space provision should be made for strike cameras as per A/C 25203 (71/FAR/49, to be issued), and missile launch cameras as per A/C 25205, (71/FAR/46). Time correlation between cameras and oscillograph recorders should be provided for.

