QC Auro CF105 Ext. A97-A.C. MAN-4

1

Secret Extract 72/Comp A/1

Dynamic The Dynamic Tuel Flow For The Avro Arrow

September 1957

T. F. Potts

72/ Comp. A/1 ORT NO Extract A97/A.C. Man/4

PREPARED BY T. F. Potts Sept. 1957 CHECKED BY , DATE 1 Sept. 1957 R. R. Carley


Arrow II

AIRCRAFT

Dynamic Manoeuvers

This report presents graphical solutions of the performance equations for the Arrow II aircraft, for the various initial conditions and constraints tabulated in the Index. The solutions were not restricted by any altitude or speed limitations, but turns were confined to 180° . Errors should not constitute more than a 5% deviation with respect to the information used for thrust, drag etc.

Geometry and Equations of Motion:



EFFECTS OF & NOT INCLUDED.

$$\vec{F} = \frac{d(m\vec{V})}{dt} = \frac{d(m\hat{V}\hat{s})}{dt} = \hat{I}\frac{d(mV)}{dt} + \hat{I}mV\hat{\theta}$$

$$= \hat{I}\frac{d(mV)}{dt} + mV\frac{d\hat{I}}{dt} = \hat{I}\frac{d(mV)}{dt} + \hat{I}mV\hat{\theta}$$

$$= \hat{I}[(T-D) - W \sin\psi\sin\theta] + \hat{I}[L\cos\phi - W\sin\psi\cos\theta]$$

AERO / M. E. LIBRARY

89- 05-1

BIBLIOTHEQUE AÉRO / G.M.

FOR CONSTANT MASS, THE EQUATIONS TO BE SOLVED ARE

(2)
$$\dot{\theta} = \frac{8}{WV} [nW\cos\phi - W\sin\psi\cos\theta]$$

Classification cancelled/changed to

DATE

AIRCRAFT

row II

T. F. Potts
CHECKED BY

Sept. 1957

Arrow II

Dynamic Manoeuvers

R. R. Carley

Sept. 1957

Thrust Mechanization:

Maximum thrust for two Iroquois engines with maximum afterburners was used throughout the program. The values of 2FN were obtained from the product $2F_N^*$, F_N where $2F_N^*$ and F_N/F_N^* are functions of Mach number

and altitude respectively. This product yields values of $2F_N$ which are everywhere within 2.5% of the values given by the carpet, and over most of the range the error is considerably less than this value.

The function $2F_N^*$ was generated as a smooth curve in the mechanization, but the function F_N/F_N^* was broken down into sixteen straight line segments. This introduces an error which nowhere exceeds 0.4% and is generally much lower than this figure.

Drag Mechanization:

Six separate drag functions were mechanized to cover the entire range of altitude and Mach numbers, and these functions were automatically switched by means of relays actuated by the parameters of the equations. Since variations of up to \pm 5% could be encountered in the values of D/p_a at switching, a lag network of transfer function 1/(1 + .ls) was introduced to smooth these discontinuities out.

The drag equation for M=0.8 to M=2.1, all altitudes is

$$\frac{D}{P_B} = A + B^2 \left(\frac{nW}{P_A} \times 10^{-4} - \frac{C}{B} \right)^2$$

where A, B^2 and $\frac{C}{B}$ are functions of Mach number, generated in straight

line segments, as shown in the appendix. Four separate functions of A, B^2 and C/B were generated to allow for values of $nW/p_a > 35,000$ and $nW/p_a < 35,000$ with allerons deflected and allerons not deflected. Allerons were deflected at 45,000 ft. for increasing altitude and returned to neutral at 42,000 ft. for decreasing altitude.

For speeds below M = 0.8, two further drag equations were mechanized, as follows:

(1) $0 \le nW/p_a \le 41,100 M^2 ---- D/p_a = 1000 M^2 + 2.4 \times 10^{-6} (nW/Mp_a)^2$

(2)
$$nW/p_a > 41,100 M^2 ---- D/p_a = -500M^2 + 3.3 \times 10^{-6} (nW/Mp_a)^2$$

These equations are for ailerons in neutral position only. No equations were mechanized for ailerons deflected, since Mach numbers below 0.8 were not anticipated at altitudes above 42,000 ft.

UNCEASSIFIED

TECHNICAL

AIRCRAFT

Arrow II

Dynamic Manoeuvers

DEPARTMENT

SHEET NO 3	1.
MELTSCILLED	DATE
T. F. Potts	Sept. 1957
CHECKED BY .	DATE
R. R. Carley	Sept. 1957

This drag mechanization is valid only for C.G. position at 29.5% MAC.

For manoeuvers with missiles lowered an additional drag increment as given by the following should have been included.

(1)
$$0 \le M \le 1.0 - \Delta D/p_a = 681 \text{ M}^2$$

(2)
$$1.0 \le M \le 2.1 - --- \Delta D/p_B = 866 M^2$$

This additional missile drag was omitted because of lack of computing equipment.

Mechanization of (nW/pa)max.:

The maximum value of nW/ $p_{\rm B}$ was generated as a smooth curve through the points listed in the appendix. The values are limited by the buffet boundary for M < 1.08 and by available trim for M > 1.08. Hinge moment limitations were not considered, and since n was limited to 5.5 'g' they were seldom exceeded. Hinge moment limitations may be found in P/Contgol/105 -- Trim angles and Flight envelope limitations, (Elastic Aircraft).

Fuel-Flow Mechanization:

Rate of fuel consumption for two Iroquois engines at maximum afterburner is obtained from the equation

$$2W_{\mathbf{f}} = 2W_{\mathbf{f}}^* \cdot \frac{W_{\mathbf{f}}}{W_{\mathbf{f}}^*}$$

where 2 % and W_f/W_f are functions of Mach number and altitude respectively. Fuel flow is limited to a maximum rate of 35.5 lb./sec.

It was at first attempted to take the changing mass of the aircraft due to fuel consumption into account in the dynamic equations, but this was discontinued when it was found that the extra computing errors introduced by the equipment were greater than the increase in accuracy gained.

The error introduced by neglecting the change in mass does not exceed 3% for the manoeuvers performed, and is usually less than this value.

Data for all of the above mechanizations was obtained from Mr. T. Roberts of Performance Group.



AVRO AIRCRAFT LIMITED MALTON - ONTARIO

TECHNICAL DEPARTMENT OF THE STEEL OF THE STE

D SHEET NO. 4

PREPARED BY DATE

T. F. Potts
CHECKED BY DATE

R. R. Carley Sept. 1957

. 1

Arrow II

AIRCRAFT:

Dynamic Manoeuvers

Appendix

1: List of Symbols:

Symbol	Description	Units
A _B 2	function of Mach No., used in drag mechanization	in ²
C/B	11 11 11 11 11 11 11	
D	total aircraft drag	1b.
2FN	thrust of two Iroquois engines, max. afterburner	1b.
2FN F _N /F _N	function of Mach No., used in thrust mechanization	1b.
Н	altitude	ft.
L	total aircraft lift	1b.
М	Mach number	
T	aircraft thrust	1b.
· v	aircraft forward speed	ft./sec
W	aircraft weight	1b.
Wr	weight of fuel consumed (on curves from computer)	1b.
2 1/2	rate of fuel consumption, both engines	lb./sec
Wf/Wf	function of Mach No., used in fuel-flow mechanization " altitude " " " "	lb./sec
a	speed of sound	01 /
	acceleration due to gravity	ft./sec2
Ę	unit vector parallel to air craft motion	It./sec
m	aircraft mass	al
n	load factor	slugs
ñ	unit vector perpendicular to $\hat{\imath}$, in manoeuver plane	
Pa	ambient atmospheric pressure	1b./in2
s	distance along aircraft trajectory	ft.
t	time	sec.
y}	Cartesian co-ordinates of aircraft trajectory in the manoeuver plane	
ok	angle of attack	don
θ	angle turned in manoeuver plane	deg.
ø	roll angle	deg. '
ψ	angle of inclination of manoeuver plane to horizontal	deg.
7		deg.

UNCARSIFIED

ET:	The Land Market of the Land Mark	U	NU	LH92	TIL
	TECHNICAL D	EPARTMEN	MA	THEC	TEIE
	TECHNICAL D	RCRAFT LIA	MITED.	FCDE	+ "

T. F. Potts Sept. 1957
CHECKED BY DATE

Arrow II

AIRCRAF

Dynamic Manoeuvres

R. R. Carley Sept. 1957

2. Drag Function

Case (1) Ailerons Deflected

(a) nW/pa > 35,000

M	<u>A</u>	M	В2	M	CIR
0.8 1.0 1.1 1.2 1.3 1.4 1.8 1.9 2.0 2.1	0 2750 4300 5500 6600 7600 10500 11500 12850 13750	0.8 0.95 1.05 1.15 1.325 1.40 1.50 1.60 1.75 2.10	414 425 442 470 526 547 479 428 372 256	0.80 0.90 1.00 1.05 1.30 1.35 1.40 1.60 1.75 2.10	.08 .50 1.25 1.42 2.49 2.78 2.90 2.58 2.50 2.50
(b) nW/	Pa 4 35,000				C
<u>M</u>	A	M	<u>B2</u>	M	<u>E</u>
0.80 1.05 1.10 1.15 1.20 1.40 1.50 1.60 1.80 2.10	0 2700 3400 3950 4410 6000 6800 7700 95 75 2,950	0.8 0.9 1.0 1.1 1.2 1.3 1.4 1.5 1.6 1.7 1.8 1.9 2.0 2.1	342 311 280 250 223.5 200 180 166.3 161 162 169 182 195 208		.9M61

UNCLASSIFIED

TECHNICAL DEPARTMENT

Extract A97/A.C. Man./4
REPORT No. 72/Comp. A/1

1.35

SHEET NO ______6

AIRCRAFT:

Arrow II

Dynamic Manching 5433 F Forts

Sept. 1957
BY DATE

DATE

R. R. Carley Sept. 1957

Case (2) Ailerons Neutral

(a) $nW/p_a > 35,000$

0.8 700 0.8 415 0.8 0 0.9 1100 0.9 422 1.25 2.15 1.0 2400 0.95 428 1.275 2.24	<u>M</u>	<u>A</u>	<u>M</u>	<u>B</u> ²	M	C
1.15 5300 1.00 436 1.3 2.28 1.2 5900 1.05 450 1.325 2.30 1.25 6350 1.1 470 1.35 2.32 1.35 6950 1.2 512 1.375 2.31 1.75 8950 1.225 522 1.4 2.31 1.85 9800 1.25 528 1.45 2.25 2.10 13300 1.275 530 1.5 2.17 1.3 526 1.55 2.06 1.35 509 1.7 1.61 1.5 446 1.75 1.46 1.8 304 1.775 1.394	0.9 1.0 1.15 1.2 1.25 1.35 1.75 1.85	1100 2400 5300 5900 6350 6950 8950	0.9 0.95 1.00 1.05 1.1 1.2 1.225 1.275 1.3 1.35 1.5 1.8 1.825 1.875 1.9 2.0	422 428 436 450 470 512 522 528 530 526 509 446 304 296 292 293 296 323	1.25 1.275 1.3 1.325 1.35 1.375 1.4 1.45 1.5 1.55 1.7 1.775 1.8 1.825 1.85 1.9	2.15 2.24 2.28 2.30 2.32 2.31 2.255 2.175 2.06 1.46 1.394 1.365 1.39 1.41 1.56 1.80

(b) nN/pg(35,000

(0) 1111/	P807,000			11	9 \
<u>M</u>	<u>A</u>	_м_	<u>B</u> ²	M 19	g B
0.80	700	0.80	530	0.8	0.3
0.90	900	0.95	380	0.9	0.39
0.95	1450	1.00	345	1.0	0.46
1.00	2000	1.05	328	1.1	0.50
1.025	2450	1.10	324	1.2	0.51
1.05	2800	1.70	340	1.3	0.63
1.10	3300	1.75	338	1.4	0.93
1.40	5600	1.85	310	1.5	1.19
1.70	8400	1.95	258	1.6	1.33
2.10	12600	2.10	139	1.7	1.42
			8	1.8	1.46
				CLORETEIL	1.45
				THE DE HOOM	1.41

TECHNICAL DEPARTMENT

Extract A 97/A.C. Man./4
REPORT NO 72/Comp. A/1

SHEET NO

DATE

PREPARED BY

T. F. Potts CHECKED BY Sept. 1957

Dynamic Manoeuvres

R. R. Carley

Sept. 1957

3. Maximum NW

Arrow II

AIRCRAFT:


M	(NW) max
.2	4910
•3	10680
.4	17 6 60
•5	24900
.6	32300
.7	40300
.8	49200
.9	60000
•95	67000
1.0	73200
1.05	82000
1.10	89700
1.15	86500
1.2	86800
1.3	88800
1.4	91600
1.5	95600
1.6	100700
1.8	110100
2.0	126200

UNCLASSIFIED

No. 10 X 10 TO THE CM. 359-14L

Mass 10 X 10 TO THE CM. 359-14L

KEUSTEL SESSEN CO. WISSEN DIA.



G 9-11 L 10 X 10 to the 55 inch, 5th lines accented PARE IN CANADA

MAS 10 X 10 TO THE 12 INCH 359-11L

G 9 - 11 L

10 X 10 to the 32 inch, 5th lines accented

MADE IN CANADA

G 9-11 L

10 X 10 to the 35 inch, 5th lines accented
MADE IN CANADA

.

G 9-11L 10 X 10 to the \\ \frac{1}{2} \text{ inch, 5th lines accented} \\ \text{RADE IN CARADA} \\ \text{RADE IN CARADA} \\ \end{align*


G 9 - 11 L

10 X 10 to the ½ inch, 5th lines accented

HARDE IN CANADA

G 9 - 11 L 10 X 10 to the ½ inch, 5th lines accented MADE IN CANADA

DISTRIBUTED BY RAPID BLUE PRINT LTD. . HAMILTON, ONT.



G 9 - 11 L

10 X 10 to the 3½ inch, 5th lines accented MADE IN CARADA

£ (356.1

G 9-11L
10 X 10 to the ½ inch, 5th lines accented

. 0

MATE REUFFEL & ESSERICO. MADEIN 19 3.4

G 9 - 11 L

10 X 10 to the ½ inch, 5th lines accented

HADE IN CAMADA