QCX AVro CF105 R-7-0400-44 Iss-1

FILE IN VAULT

75 P3 Engines

Report # 7-0400-44 Issue 1

WEIGHT SUMMARY & C.G. POSITION

F. 8 SECRET Dec. 1/5

1 *	National Research Council Canada C.I.S.T.I. Aeronautical and Mechanical Engineering Library Conseil national de recherches Canada I.C.1.S.T. Bibliotèque d'aéronautique et de génie mécanique DATE JAN 0 7 1993
	Report no.: OCX-AVRO-CF105- R-7-0400-44-I55-1 has been downgraded to: XX de-classified
	by (Name): Michel W. Drapeau (Dept.): A/DND Coordinator, Access to Information Date: Dec. 7, 1992
	Signature
	Classification cancelled / changed to: UNCLASSSIFIED By authority of: DRDA 7/DARFT 5-8/DAS Eng 6-4-5 Date: 5 Nov 1992 Signature: B. Authory Unit / Rank / Appointment: DSIS 3, Secretary CRAD HQ DRP

Date: December 1st, 1956 Aircraft: C-105 1st. A/C With J75 P3 Engines



Report # 7-0400-44 Sheet # 1 Issue 1 Prepared By: K. Griffin Checked By: E. Burnett

INTRODUCTION

The following is a preliminary Weight & C.G. Summary for the 1st C-105 Aircraft with J75 P3 Engines.

Information herein is based on Report # 7-0400-05 Issue 27, December 1st, 1956, Weight Summary for C-105 Production Aircraft with J75 P5 Engines as Interim Power Plant, with relevant changes made.

Note: This Summary doen Not apply for the 2nd and subsequent aircraft - see

GENERAL

- (a) Pratt & Whitney J75 P3 Engines comprise the Power Plant for the 1st Aircraft. J75 P5 Engines which are partially redesigned versions of the P3 Engines are to be installed on the 2nd and subsequent aircraft.
- (b) An instrument package carrying Flight Test Instrumentation will be installed, this also varies between first and subsequent aircraft.
- (c) An interim Radio & Radar System is installed.

1.	STRUCTURE:	WEIGHT (1b)

Basically this is unchanged from the J75 P5 Production Aircraft, however, there are some changes as follows:-

- Radome Solid fibreglass laminate will be installed, the honeycomb laminate is unavailable for the early aircraft. + 103
- Radar Nose Structure Current weight recorded for Production Aircraft is actually that for the 1st Aircraft. The Production nose will be different, but no details yet available.
- Centre Fuselage Cover Panel replaces .28" thick fibreglass panel in Electronics Bay. 7
- Rear Fuselage Stainless Steel of a similar gauge will replace titanium for the Nacelles, Stinger, & Slitter assemblies. The tunnel skins from Sta. 742.5" to 803" remain unchanged in titanium.

Weight penalties are as follows: Nacelles + 122
Stinger + 17
Slitter + 5

There will possibly be other substitutions of Steel for Titanium in the Engine Bay etc. but no details are yet known.

The first Aircraft will also have numerous salvage schemes, re-works etc. incorporated which will account for a weight increase the size of which it is impossible to currently assess.

Weight Change Structure Compared to 7-0400-05 Issue 27

+ 240

Date: December 1st, 1956 Aircraft: C-105 lst. A/C

With J75 P3 Engines NON

Report # 7-0400-44 Sheet # 2 Issue 1 Prepared By: K. Griffin Checked By: E. Burnett


INTRODUCTION

		INTRODUCTION		
2.	LANDING GEA	<u>R</u>	WEIGHT	(lb)
	Main Underca	arriage - Tubeless Tyres will not be available for the early aircraft and conventional tyres & tubes will be fitted resulting in + 2 lb per wheel assy.	+	8
		Weight Changes Landing Gear compared to 7-0400-05 Iss. 2	7 +	8
3.	POWER PLANT	& SERVICES		
	Engines -	On the 1st Aircraft only, J75 P3 Engines will be installed, these weigh approximately 6,175 lb compared to the 5,950 lb of the J75 P5 Engines for the 2nd and subsequent aircraft.	+	450
	Fuel System	- The 1st Aircraft will be fitted with fuel proportioners, 2nd Aircraft may have both proportioners and a selection system fitted. Production versions will probably only have a selection system. Since details of the selection system are not available, the weight currently carried for all versions of the C-105 J75 Aircraft is for a proportioner system.		
		Weight Change Power Plant compared to 7-0400-05 Iss. 27	+	450
4.	FLYING CONT	ROLS GROUP		
	This will remain as in Report 7-0400-05 Issue 27			
5.	. EQUIPMENT GROUP			
	The 1st Air	craft will carry an instrument package the structural weight of which is This replaces the Missile Package Flight Test Instrumentation Pack Ejection - 1st A/C only Telecommunication Pack - 1st A/C only The Astra I Radar System is deleted Interim Radio & Radar is installed Additional Fire Protection is provided Weight Change Equipment compared to 7-0400-05 Iss. 27	- 1 + 2 +	671 ,893 ,322 100 25 ,850 757 155

6. OPERATIONAL LOAD

All items as in Report 7-0400-05 Iss. 27 with the following alteration:

- 1,728 Missiles - these are Not carried Weight Change Operational Load compared to 7-0400-05/27 . - 1,728



INTRODUCTION

SUMMARY (All Changes Relative to Report 7-0400-05 Issue 27 C-105

Production Aircraft with J75 P5 Engines as Interim
Power Plant.

Structure + 240 lb.
Landing Gear + 8 lb.
Power Plant + 450 lb.
Equipment - 713 lb.

- 15 lb.

Weight Change - Operational Load - Less Fuel

Missiles - 1,728 lb.

Weight Change - Operational Weight Empty - (A/C Less Fuel)

Report # 7-0400-05 Issue 27 Report # 7-0400-44 Iss. 1

46,528 44,785 = 1,743 lb.

UNCLASSIFIED NON CLASSIFIE

Report # 7-0400-44 Sheet # 4 Issue 1 Prepared By: K. Griffin

Cr-

WEIGHT AND C.G. SUMMARY

73	SECRET		
UNCLASSIFIED	WEIGHT	H. ARM	V. ARM
UNCLASSIT	_lb	ins.	ins.
CERTICALIER NON CLASSIFIE		27100	21100
STRUCTURE	18,326.94	564.61	137.10
Wing	9,989.07	643.60	141.93
Fin and Rudder	999.96	754.27	201.96
Fuselage Structure Fwd. 255"	2,493.41	181.34	128.81
Sta. 255" - 485"	1,664.90	379.04	130.01
Aft. Sta. 485"	3,179.60	654.56	111.73
UNDERCARRIAGE - Up Position	2,612.33	488.80	134.66
Main Undercarriage	1,959.62	539.48	141.00
Main Undercarriage Doors & Fairings	294.36	539.29	136.01
Nose Undercarriage	333.81	170.80	99.70
Nose U/C Door & Fairing	24.54	162.24	88.23
POWER PLANT & SERVICES	14,168.53	654.68	120.21
Engines	12,672.03	663.97	119.76
Gear Box Installation on Fuselage	237.06	603.73	104.00
Gear Box & Starter on Engine	150.18	610.55	96.37
Engine Controls	29.19	377.46	7118.91
Engine De-Icing	70.37	562.80	115.09
Fire Extinguisher System	70.52	701.99	127.72
Engine Mountings	189.19	633.40	127.82
Fuel System	749.99	542.97	135.70
FLYING CONTROLS GROUP	1,677.82	688.36	139.58
Mechanical Flying Controls	904.40	689.05	147.08
Hydraulic Flying Controls	773.42	687.56	130.81
EQUIPMENT - FIXED & REMOVABLE	7,033.27	377.92	110.22
Instruments	53.30	153.98	140.27
Probe	23.00	9.74	108.00
Cockpit Pressure Sealing	5.00	186.00	130.00
Oxygen System	43.44	227.72	142.18
Air-Conditioning System	712.69	327.16	133.26
Surface Finish	100.00	591.52	140.20
Hydraulics Main System	588.36	501.22	117.38
Cabin Insulation	11.91	179.24	130.00
Brake Parachute	69.69	784.88	131.17
Electrical System	955.20	403.43	116.21
Low Pressure Pneumatics	39.01	478.47	127.28
Oil & Hydraulic Fluid Cooling	22.00	579.50	92.00
Intake De-icing	85.84	206.52	118.79
Canopy Actuation	54.41	222.04	154.40
Cabin Consoles	20.65	117.37	125.23
Radar Door Actuation	10.00	268.00	95.00
Ejector Seats	186.00	201.10	136.25
Interim Radio & Radar	756.70	297.30	118.00
Instrument Pack Structure	670.61	385.90	94.71
Instrumentation - 1st A/C	2,447.00	389.50	95.00
Additional Fire Protection	155.00	434.05	103.06
Radome Anti-icing	23.46	62.92	126.04
AIRCRAFT WEIGHT EMPTY	43,818.89	563.99	127;27

SECRET

Report # 7-0400-44 Sheet # \$ Issue 1 Prepared By: K. Griffin

WEIGHT AND C.G. SUMMARY

SECRET

DESCRIPTION		WEIGHT lb.	H. ARM ins.	V. ARM ins.	C.G. POSITION % M.A.C.
USEFUL LOAD (Less Fuel)		964.18	353.79	132.91	
Crew Oil Alcohol - Radome De-Icing Engine Fire Extinguisher Flui Residual Fuel Oxygen Charge Water For Air-Conditioning	id	430.00 130.39 22.00 25.00 218.40 13.39 125.00	194.00 609.19 93.00 730.00 553.98 259.69 268.00	136.50 117.17 138.00 129.00 134.04 159.91 132.00	
Operational Weight Empty	U/C Up U/C Down	44,783.07	559.46 561.63	127.39 123.79	34.10 34.70
Max. Internal Fuel (2,544 gal @ 7.8 lb/gal.	L 0	19,843.00	538.88	144.32	
A.U.W. Max. Internal Fuel	U/C Up U/C Down	64,626.07	553.14 554.64	132.59 130.09	32.35 32.77
Max. External Fuel & Tank 500 gals. at 7.8 lb/gal		4,226.00	522.34	60.64	
A.U.W. Max. Internal & Extern	U/C Up nal U/C Down	68,852.07	551.92 552.66	128.17 125.83	32.02 32.22

N. B. Above figures are for the Aircraft in the unballasted condition.

If the most aft point on the flight C.G. Envelope is to be ballasted to 31% M.A.C. then 1,438 lb of ballast must be installed at A/C Sta. 100%.

UNCLASSIFIED NON CLASSIFIE

KAS 10 X 10 TO THE 1/2 INCH

SECRET

