

FOURTH EDITION

Price
\$100

Part No. 24751
Printed in U.S.A.



HOMELITE®

XT2[®]
Automatic

Chain Saw

OWNERS MANUAL

SPECIFICATIONS and INFORMATION

Engine Type	2-cycle, loop-scavenged with Power Boost™ combustion chamber.	Breaker Point Gap015" (0.38 mm)
Dry Weight	7 lb., 3 oz. (3.26 kg)	Coil-to-Rotor Gap008"-.012" (0.20 mm-0.30 mm)
Displacement	1.6 cu. in. (26.2 cc)	Spark Plug	Champion DJ-7J
Bore and Stroke	1-5/16" x 1-3/16" (33,34 mm x 30, 16 mm)	Spark Plug Gap025" (0.64 mm)
Cutting Speed	5,000-10,000 rpm	Chain Oil Capacity	6.1 U.S. fl. oz. (180 cc)
Idle Speed	2900-3200 rpm	Chain Oil System	Automatic positive displacement, piston pump. Pressurized tank.
Bearings	Crankshaft, needle; connecting rod, aluminum and needle.	Chain Oil Filter	Cleanable, screen in tank
Connecting Rod	One piece, hardened steel	Air Filter	Polyurethane sponge (replace when dirty)
Starter	Rewind, nylon rope, one piece pulley	Carburetor Type	HDC-15 w/fuel pump
Clutch	One piece centrifugal automatic	Intake Valving	Stainless steel reed valve into crankcase
Muffler	Soffione™ diffuser type	Fuel Tank Capacity	8.15 U.S. fl. oz. (250 cc)
Throttle Control	Twin Trigger™ Dual Control System	Fuel Filter	Flexible pick-up, replaceable filter
Ignition Magneto	Conventional Breaker Point Magneto System	Continuous Operating Time per Filling	Up to 15 minutes
Ignition Timing	23° BTDC		

™ — Trademark of Homelite, a Division of Textron Inc.

HOMELITE®

A **textron** DIVISION

14401 CAROWINDS BLVD.

P.O. BOX 7047, CHARLOTTE, N.C. 28217