LINTEL - 3 LS 5"X3½"X5/16" 5'-0" LG.
PRESSED STEEL CASING AND JAMB LINING AT SALT GLAZED BLOCK
3'-4"X7'-0" H.M. DOOR
P.S. FRAME
ELEVATION - ROOM SIDE OF EXIT DOOR - SECOND STORY
SCALE 1/4"=1'-0"
CUT NEW OPENING THRU WALL PROVIDE NEAT CUT AT SALT GLAZED WAINSCOT. SEE DETAIL ABOVE
PRESSED STEEL JAMB LINING AND CASING
NOTE: OWNER TO REMOVE LOWER PART OF PUNCHING BAG FRAME
FILL IN FLOOR WITH FLUSH CEMENT UP TO WOOD FLOOR
EXISTING WALL
NEW 4" DS
WALL RAIL
THRESH
CEM. SILL
CEM. IN TREADS. N.S. ABRASIVE
3'-4"X7'-0"X1¾" H.M. DOOR PRESSED STL. FRAME 1½ HR RATING
CEM. FL. N.S. ABRASIVE
1¼" D.P. PIPE RAIL
CEM. FL
NON SLIP ABRASIVE
NEW 8X8" GL. BL. OPNG
8" CONC. BLOCK
4" BRICK
PLAN - SECOND STORY
ROOF STEEL
REMOVE WINDOW 8" BRICK IN OPNG.
HEATING CONVECTOR TO REMAIN
PLASTERED
REMOVE WINDOW. CUT OPNG TO FLOOR. FILL IN AT FLOOR WITH LINOLEUM PATCH.
EXISTING CONVECTOR UNDER WINDOW TO BE REMOVED AND PIPES REMOVED AND PLUGGED.
REPAIR PLASTER
THRESH.
4" BRICK
CEM.
D 22 R
3'-4"X7'-0"X1¾" H.M. DOOR P.S. FRAME
3" SLAB STD CORRUFORM 6X6-6/6 MESH
1¼" PIPE RAIL
CEM
8"X12 GL. BL. OPNG.
UP 12 R
SECT BB
PLAN - FIRST STORY
SCALE 1/2"=1'-0"
REMOVE WINDOW 8" BRICK IN OPNG. LOCATE IN WALL AS DIRECTED
REMOVE PRESENT WOOD DOOR FRAME AND TRANSOM. NEW PAIR 2'-6"X7'-0" H.M. DOORS AND P.S. FRAME. 8" BRICK WALL IN TRANSOM SPACE
SECT A-A
REMOVE PAIR WOOD DOORS, TRANSOM AND FRAME. NEW PAIR.
UP 22 R
10'-0"
23'-0"
THRESHOLD
PAIR 2-6X7-0X1¾" H.M. DOORS + P.S. FRAME
PLAN - GROUND STORY
SCALE 1/2"=1'-0"
1/4" P.F. SLOPE
ROOF 3 PLY SMOOTH SURFACE ¾" INSULATION 1½" 22 GA STL DECK
NEW LINTEL
10X10 POL PLT WIRE GL.
FIN. 2ND FL.
CEM. SILL ALUM.
Glass block
BRICK FLUSH ON SOUTH SIDE
NEW LINTEL
10'-10½"
12'-8"
8" BRICK IN OPNG.
8" BRICK IN TRANSOM
NEW LINTEL
13'-6"
8'-8"
EXISTING 2ND FL
EXISTING 1ST FL
EXISTING GR. FL
4" SLAB
13'-10
Fire Escape
Sheet 2