DEPARTMENT OF COMMERCE

STEAMBOAT-INSPECTION SERVICE

RULES FOR LIGHTS FOR FERRYBOATS, AND FOR BARGES AND CANAL BOATS IN TOW OF STEAM VESSELS, AND FOR DAY SIGNALS FOR DREDGES, VESSELS WORKING ON WRECKS, ETC., NAVIGABLE HARBOR FOR LIGHTS AND DAY SIGNALS FOR OTHER INLAND WATERS OF THE UNITED STATES, EXCEPT THE GREAT LAKES, AND HARBORS, RIVERS, AND TRIBUTARY WATERS AS FAR EAST AS MOBILE, ALABAMA, AND INTO LAKES AND THEIR CONNECTING AND TRIBUTARIES. THE RULES FOR LIGHTS AND DAY SIGNALS FOR VESSELS ENTERING INTO AND THE RED RIVER OF THE NORTH AND RIVERS EMPTYING INTO THE GULF OF MEXICO AND THEIR TRIBUTARIES.

Authority: Section 2, Act of Congress approved June 7, 1897.

The following rules are as amended by the Board of Supervising Inspectors, Steamboat-Inspection Service, which rules have been approved by the Secretary of Commerce, and are effective on and after September 1, 1914.

These rules concerning lights shall be complied with in all weathers from sunset to sunrise.

LIGHTS TO BE CARRIED BY FERRYBOATS.

Ferryboats propelled by machinery and navigating the harbors, rivers, and other inland waters of the United States, except the Great Lakes and connecting and tributary waters as far east as Montreal and the Red River of the North and rivers emptying into the Gulf of Mexico and their tributaries, and except on the waters of the Hudson River as far as the Troy dam, shall carry the range lights and the regular colored side lights required by law to be carried on steam vessels navigating waters subject to the general rules. Such ferryboats shall carry a bottom range light and a top range light, each showing all around the horizon, placed at equal distances forward and aft, also one on each side showing a red light visible from right ahead to 2 points abaft the beam on the port side, and a green light so visible on the starboard side; such colored side lights must be provided with inboard screens, so as to prevent them from being seen across the bow, and so constructed as to show a uniform and unbroken light over an arc of the horizon of 10 points of the compass, and so fixed as to throw the light from right ahead to 2 points abaft the beam on their respective sides.

Local inspectors in districts having ferryboats shall, whenever the safety of navigation may require, designate for each line of such boats a certain light to be carried on the forward part of the vessel, which shall show all around the horizon, to designate and distinguish such lines from each other, which light shall be carried on a flagstaff, signalmast, or other part above the white range lights.

The green and red lights shall be fitted with inboard screens projecting at least 3 feet forward from the lights, so as to prevent them from being seen across the bow.

LIGHTS FOR BARGES AND CANAL BOATS IN TOW OF STEAM VESSELS ON CERTAIN INLAND WATERS ON THE SEABOARD, EXCEPT THE HUDSON RIVER AND ADJACENT WATERS AND LAKE CHAMPLAIN.

On the harbors, rivers, and other inland waters of the United States, except the Great Lakes and their connecting and tributary waters as far east as Montreal and the Red River of the North and rivers emptying into the Gulf of Mexico and their tributaries, and except on the waters of the Hudson River as far as the Troy dam, from a line drawn across the entrance of Gardiners Bay between Orient Point and Plum Island, to the Atlantic Ocean, and including Narragansett Bay, R. I., and tributaries, and Lake Champlain, barges of seagoing construction, and canal boats in tow of steam vessels, shall each carry a green light on the starboard side and a red light on the port side, each showing a white light for a distance of at least 2 miles, and so constructed as to show a uniform and unbroken light over an arc of the horizon of 10 points of the compass, namely, for 6 points from right aft on each side of the vessel, so fixed as to throw the light from right ahead to 2 points abaft the beam on their respective sides. On the after end of the outside boats, and so placed as to be seen as far astern as possible, there shall be carried one white light, so constructed as to show a uniform and unbroken light over an arc of the horizon of 12 points of the compass, namely, for 6 points on each side of the vessel from right astern, and so placed as to show astern. Such boats shall be towed by a hawser not exceeding 15 fathoms in length, and no towing hawser between them shall be used. When barges and canal boats are towed alongside of the steamer, they shall carry a white light at each end of the hawser between the steamer and the tow, and shall show the colored side lights required to be carried by steam vessels, when towing singly or when towed alongside of steamers.

Barges and canal boats towing alongside a steam vessel, or towed astern by a hawser not exceeding 15 fathoms in length, shall carry the colored side lights required to be carried by steam vessels, when towing singly, or when towed alongside of steamers, and shall also carry a white light at the stern of the outside boat.

Barges and canal boats towed astern by a hawser more than 15 fathoms in length shall carry a white light at each end.

Barges and canal boats towed alongside a steam vessel, if on the starboard side of said steam vessel, shall display a white light on her own starboard bow and if on the port side of said steam vessel shall display a white light on her own port bow; and if there is more than one barge or canal boat towed alongside, the white lights shall be displayed from the outboard side of the outside barge or canal boat: *Provided*, That barges known as car floats when towed alongside shall have a white light at each outboard corner of the outside car float.

When barges or canal boats are massed in tiers and towed at a hawser, as is usual on the Hudson River, there shall be carried on the forward port side of the port boat of the outside tier a white light, and on the forward starboard side of the starboard boat in each tier a white light, and on the after port side of the port boat in the stern tier a white light, and on the after starboard side of the starboard boat in the stern tier a white light.

The white bow lights required to be carried by the preceding rules shall be carried at least 10 feet and not more than 30 feet abaft the stem or extreme forward end of the vessel. On barges and canal boats required to carry a white bow light, the white light on bow and the white light on stern shall each be so placed as to show from right ahead to 2 points abaft the beam on both sides, and shall each be of such a character as to be visible on a dark night with a clear atmosphere at a distance of at least 5 miles.

Provided, That nothing in these rules shall be construed as compelling barges or canal boats in tow of steam vessels, passing through any waters coming within the scope of these rules where lights for barges or canal boats are different from those of the waters whereon such vessels are usually employed, to change their lights from those required by the rules from which they enter, when such barges or lumberpassing different lights from those where they are customarily employed, they shall comply with the local rules whose employed.

LIGHTS FOR BARGES AND CANAL BOATS IN TOW OF STEAM VESSELS ON THE HUDSON RIVER AND ADJACENT WATERS AND LAKE CHAMPLAIN.

All nondescript vessels known as scows, car floats, lighters, and vessels of similar type, navigating the waters referred to in the following rules, shall carry the lights required to be carried by barges and canal boats in tow of steam vessels, as prescribed in such rules.

Barges and canal boats, when being towed by a steam vessel on the waters of the Hudson River and its tributaries from Troy to the boundary lines of New York Harbor as defined by law, and pursuant to section 2 of the act of Congress of February 19, 1895, the East River, and Long Island Sound (and the waters entering thereon, and to the Atlantic Ocean), and including Narragansett Bay, R. I., and tributaries, and Lake Champlain, barges of seagoing construction and canal boats in tow of steam vessels shall each carry a green light on the starboard side and a red light on the port side, each showing a white light for a distance of at least 2 miles, and so constructed as to show a uniform and unbroken light over an arc of the horizon of 10 points of the compass, namely, for 6 points from right aft on each side of each vessel, so fixed as to throw the light from right ahead to 2 points abaft the beam on their respective sides. On the after end of the outside boats, and so placed as to be seen as far astern as possible, there shall be carried one white light, so constructed as to show a uniform and unbroken light over an arc of the horizon of 12 points of the compass, namely, for 6 points on each side of the vessel from right astern, and so placed as to show astern. Such boats shall be towed by a hawser not exceeding 15 fathoms in length, and no towing hawser between them shall be used. When barges and canal boats are towed alongside of the steamer, they shall carry a white light at each end of the hawser between the steamer and the tow, and shall show the colored side lights required to be carried by steam vessels, when towing singly, or when towed alongside of steamers.

Barges and canal boats towing alongside a steam vessel, or towed astern by a hawser not exceeding 15 fathoms in length, shall carry the colored side lights required to be carried by steam vessels, when towing singly, or when towed alongside of steamers, and shall also carry a white light at the stern of the outside boat.

Barges and canal boats towed astern by a hawser more than 15 fathoms in length shall carry a white light on the stern and a white light on the stern of each of the outside boats; when in more than one tier, each of the outside boats shall carry a white light on its bow; and the outside boats in the last tier shall each carry, in addition, a white light on the starboard side.

Barges or canal boats towed alongside a steam vessel, if on the starboard side of said steam vessel, shall display a white light on her own starboard bow, and if on the port side of said steam vessel shall display a white light on her own port bow; and if there is more than one barge or canal boat towed alongside, the white lights shall be displayed from the outboard side of the outside barge or canal boat: *Provided*, That barges known as car floats when towed alongside shall have a white light at each outboard corner of the outside car float.

When barges or canal boats are massed in tiers and towed at a hawser, as is usual on the Hudson River, there shall be carried on the forward port side of the port boat of the outside tier a white light, and on the forward starboard boat in each tier a white light, and on the after port side of the port boat in the stern tier a white light, and on the after starboard side of the starboard boat in the stern tier a white light.

The white bow lights required to be carried by the preceding rules shall be carried at least 10 feet and not more than 30 feet abaft the stem or extreme forward end of the vessel. On barges and canal boats required to carry a white bow light, the white light on bow and the white light on stern shall each be so placed as to show from right ahead to 2 points abaft the beam on both sides, and shall each be of such a character as to be visible on a dark night with a clear atmosphere at a distance of at least 5 miles.

Provided, That nothing in these rules shall be construed as compelling barges or canal boats in tow of steam vessels, passing through any waters coming within the scope of these rules where lights for barges or canal boats are different from those of the waters whereon such vessels are usually employed, to change their lights from those required by the rules from which they enter, when such barges or lumberpassing different lights from those where they are customarily employed, they shall comply with the local rules whose employed.

RULES FOR LIGHTS AND DAY SIGNALS FOR VESSELS, DREDGES OF ALL TYPES, AND VESSELS WORKING ON WRECKS OR OTHER OBSTRUCTIONS TO NAVIGATION, OR MOORED FOR SUBMARINE OPERATIONS OR SUBMARINE CONSTRUCTION OR SUNKEN OBJECT WHICH MAY DRIFT WITH THE TIDE OR BE TOWED.

RULE 1. RULE FOR SIGNALS TO BE DISPLAYED BY A TOWING VESSEL WHEN TOWING A SUBMERGED OR PARTLY SUBMERGED OBJECT UPON A HAWSER WHEN NO SIGNALS ARE DISPLAYED UPON THE OBJECT WHICH IS TOWED.

The vessel having the submerged object in tow shall display by day, where they can best be seen, two shapes, one above the other, not less than 6 feet apart, the lower one of which shall be carried not less than 10 feet above the deck house. The shapes shall be in the form of a double frustum of a cone, base to base, not less than 2 feet in diameter at the center nor less than 8 inches at the ends of the cones, and to be not less than 4 feet apart from end to end, and the upper shape to be painted in alternate black and white, 8 inches in width, and the lower shape to be painted a solid bright red.

By night the towing vessel shall display the regular side lights, but not more than one pair of colored lights, and the upper white range light shall not less than 6 feet above the deck house, and in addition thereto there shall be displayed a white light from the bow and stern of each outside vessel or lighter not less than 6 feet vertical line not less than 6 feet and not more than 15 feet above the deck.

RULE 2. RULE FOR SIGNALS. DREDGES, LIGHTERS, OR OTHER TYPES OF VESSELS MADE FAST ALONGSIDE A WRECK, OR MOORED OVER A WRECK WHICH IS ON THE BOTTOM OR PARTLY SUBMERGED, OR WHICH MAY BE DRIFTED.

Steamers, derrick boats, lighters, or other types of vessels made fast alongside a wreck, or moored over a wreck which is on the bottom or partly submerged, or which may be drifting, shall display by day, where they can best be seen, two shapes, one above the other, not less than 6 feet apart, the lower one of which shall be carried not less than 10 feet above the deck house, and in such a position where they can best be seen. The shapes shall be painted a solid bright red, but where more than one vessel is working under the above conditions the shapes need be displayed only from one vessel on each side of the group, and in such a position where they can best be seen from all directions.

By night the vessel shall display the regular side lights, but not more than one pair of colored lights, and the upper red light shall be not less than 6 feet above the deck house, and in addition thereto there shall be displayed a white light from the bow and stern of each outside vessel or lighter not less than 6 feet vertical line not less than 6 feet and not more than 15 feet above the deck.

RULE 3. RULE FOR DREDGES WHICH ARE HELD IN STATIONARY POSITION BY MOORINGS OR SPUDS.

Dredges which are held in stationary position by moorings or spuds shall display by day two red balls not less than 2 feet in diameter and carried in a vertical line not less than 3 feet nor more than 6 feet apart, and at least 15 feet above the deck house and in such a position where they can best be seen. They shall display a white light at each corner, not less than 6 feet above the deck house, and in such a position where they can best be seen, but not less than 4 feet above the deck house, and in addition thereto two red lights carried in a vertical line not less than 3 feet nor more than 6 feet apart and not less than 6 feet above the deck house. When vessels are moored alongside a dredge in the foregoing situation they shall display a white light on each outboard corner, not less than 6 feet above the deck.

RULE 4. RULE FOR SELF-PROPELLING SUCTION DREDGES UNDERWAY WITH THEIR SUCTIONS ON THE BOTTOM, AND ENGAGED IN LAYING PIPE OR OPERATING ON SUBMARINE CONSTRUCTION OR EXCAVATION.

Self-propelling suction dredges underway with their suction on the bottom shall display by day two red balls not less than 2 feet in diameter, in a vertical line not less than 3 feet nor more than 6 feet apart, and not less than 15 feet above the deck house, and in such a position where they can best be seen from all directions.

By night the vessel shall carry, in addition to the regular range lights, two red lights of the same character as the masthead light, in the same vertical line and underneath the masthead light, the red lights to be not less than 4 feet nor more than 6 feet apart and the upper red light to be not less than 6 feet above the deck house, and in such position where they can best be seen from all directions.

Vessels which are moored or anchored, and engaged in laying pipe or operating on submarine construction or excavation shall display by day, in addition to the signals required by the general rules for dredges, wrecking boats, lighters, etc., shall be of such size and character as to be visible on a dark night with a clear atmosphere for a distance of at least 2 miles.

POSTING OF RULES.

On each barge, dredge, canal boats, vessels working on wrecks, and steam and other motor vessels, of over 100 gross tons, a copy of these rules shall be kept posted up in conspicuous places on each vessel, one copy of which shall be kept posted up in the pilothouse and not over 100 gross tons, and under 500 gross tons, two copies of this form shall be kept posted up in conspicuous places on each vessel, and of 500 gross tons and under, and of more than 25 gross tons, two copies shall be kept conspicuously posted up in the pilothouse. On each vessel of 25 gross tons and under, one copy thereof shall be kept conspicuously posted up in the pilothouse, and, where practicable, one copy thereof shall be kept conspicuously posted up in the vessel.