

CL OF SHEAVE
7 1/2"
10 1/2"
BOTTOM OF BLACK BAND

UPPER SHROUD-1/4" X 19'-53'-5" EYE TO FORK

SPREADER WIDTH-58 1/2" FROM CL

TOP OF SPREADER

INTERMEDIATE SHROUD-1/4" X 19'-37'-10 1/4" EYE TO EYE

SPREADER WIDTH-66 5/8" FROM CL

TOP OF SPREADER

FWD. LOWER SHROUD 1/4" X 19'-21'-11" EYE TO EYE
AFT. LOWER SHROUD 1/4" X 19'-22'-0" EYE TO EYE

TOP OF BOOM

TOP OF STEP

10'-4" APPROX.
DETERMINE BY LENGTH OF SHRODS
AND A TEMPLATE FROM THE MAST
STEP TO END OF SHRODS

NOTE NO. 1
ALL SHROUDS & BACK STAY
USE AIRCRAFT TYPE SWAGED
FITTINGS AND 3/8" SEA BRIGHT
TURNBUCKLES.
HEAD STAY USES MARINE EYE
BOTH ENDS WITH 1/2" MERRIMAN
TURNBUCKLE AND TOGGLE.

NOTE NO. 2
MAST IS 8 1/2" X 6"
IN SECTION FROM
STEP TO UPPER
SPREADER-TOP OF
MAST IS 5" X 4"
USE 1 1/4" SPRUCE
ALL AROUND

0875-7
H-47 reh.
2001 3 27 5:4

H-47
K009.010