910 A 10 A	
Cast on at each end of next row 9 9	stitches
Work in stockinette stitch (with the except-	
· of first and last two stitches in row	inches
which should be killed for the should be kille	THORSE STUDY
There should now be on needle 96 100	stitches
There should now be on head to the form of K 2 P2 for	inches
Bind off loosely, knitting the knit stitches	Town realbeau
and purling the purled stitches.	701
SI HRV H PICK UD and Knitt at Outle at mitoto	stitches
	inches
honder as inderabilit tores sees sees sees sees	THOUGH
Decrease at both ends of every 6th row by knit-	
ting together 3rd and 4th stitches from end until sleeve measures from start16. 16	I di L
end until sleeve measures arom societies 44 48	stitches
There should be	Pareson Lin
atitohas (annioximater of the factor	EWOT dl duoda
fore starting cuff.  Work in ribbing of K 2, P 2 for	dnobod
Work in ribbing of K 2, P 2 for4	inches
Bind off Loosely, Knitting the knit and putt	elese
ing the purled stitches	
stars and an enem book of neck 11 44 32 32	stitches
NECK-Pick up from back of neck	stitches
from front of neck.	Body Let
In order to have a number divisible by 4	97667G
for the ribbing, increase or decrease	
and account in next row so that there	- hd talaga
will be on needle	inches
K2, P 2 for 6 6	THEIRS
Bind off very loosely, knitting the knit and purling th	e purle
Bind off very loosely, knieding one knied and putting	Work in stoc
	Not be the file of the same of
stitches. Wor at andoreta out feel bas to	ALL IC HOL
stitches.  Mack should measure at least 22-23 inches around when s	tretche
Neck should measure at least 22-23 inches around when s	tretche
Neck should measure at least 22-23 inches around when s	tretche
Neck should measure at least 22-23 inches around when s Sew up side and armhole seams, using an overcast stit	tretche
Neck should measure at least 22-23 inches around when s Sew up side and armhole seams, using an overcast stit Press body of sweater (BUT NOT THE RIBEING) with warm i	tretche
Neck should measure at least 22-23 inches around when s Sew up side and armhole seams, using an overcast stit Press body of sweater (BUT NOT THE RIBEING) with warm in damp cloth.	ron an
Neck should measure at least 22-23 inches around when s Sew up side and armhole seams, using an overcast stit Press body of sweater (BUT NOT THE RIBEING) with warm in damp cloth.	ron an
Neck should measure at least 22-23 inches around when s  Sew up side and armhole seams, using an overcast stit  Press body of sweater (BUT NOT THE RIBEING) with warm i damp cloth.  CHAPTER LABEL should be sewed inside the back at neck o	ron an
Neck should measure at least 22-23 inches around when s  Sew up side and armhole seams, using an overcast stit  Press body of sweater (BUT NOT THE RIBEING) with warm i damp cloth.  CHAPTER LABEL should be sewed inside the back at neck o	ron an
Neck should measure at least 22-23 inches around when s  Sew up side and armhole seams, using an overcast stit  Press body of sweater (BUT NOT THE RIBEING) with warm i damp cloth.  CHAPTER LABEL should be sewed inside the back at neck o  SIZE OF SWEATER should be indicated either on Chapter 1	ron an
Neck should measure at least 22-23 inches around when s  Sew up side and armhole seams, using an overcast stit  Press body of sweater (BUT NOT THE RIBEING) with warm i damp cloth.  CHAPTER LABEL should be sewed inside the back at neck o  SIZE OF SWEATER should be indicated either on Chapter 1 on a separate tag.	ron an
Nock should measure at least 22-23 inches around when s  Sew up side and armhole seams, using an overcast stit  Press body of sweater (BUT NOT THE RIBEING) with warm i damp cloth.  CHAPTER LABEL should be sewed inside the back at neck o  SIZE OF SWEATER should be indicated either on Chapter 1 on a separate tag.  DO NOT START ANOTHER GARMENT WITH LEFT-OVER YARN.	ron an f swiit e?
Neck should measure at least 22-23 inches around when s  Sew up side and armhole seams, using an overcast stit  Press body of sweater (BUT NOT THE RIBEING) with warm i damp cloth.  CHAPTER LABEL should be sewed inside the back at neck o  SIZE OF SWEATER should be indicated either on Chapter 1 on a separate tag.  DO NOT START ANOTHER GARMENT WITH LEFT-OVER YARN.	ron an f swiit e?
Nock should measure at least 22-23 inches around when s  Sew up side and armhole seams, using an overcast stit  Press body of sweater (BUT NOT THE RIBEING) with warm i damp cloth.  CHAPTER LABEL should be sewed inside the back at neck o  SIZE OF SWEATER should be indicated either on Chapter 1 on a separate tag.  DO NOT START ANOTHER GARMENT WITH LEFT-OVER YARN.  PLEASE RETURN ALL UNUSED YARN TO CHAPTER	ron an f swiit e?
Neck should measure at least 22-23 inches around when s  Sew up side and armhole seams, using an overcast stit  Press body of sweater (BUT NOT THE RIBEING) with warm i damp cloth.  CHAPTER LABEL should be sewed inside the back at neck o  SIZE OF SWEATER should be indicated either on Chapter 1 on a separate tag.  DO NOT START ANOTHER GARMENT WITH LEFT-OVER YARN.  PLEASE RETURN ALL UNUSED YARN TO CHAPTER	ron an  f swiit ao
Neck should measure at least 22-23 inches around when s  Sew up side and armhole seams, using an overcast stit  Press body of sweater (BUT NOT THE RIBEING) with warm i damp cloth.  CHAPTER LABEL should be sewed inside the back at neck o  SIZE OF SWEATER should be indicated either on Chapter 1 on a separate tag.  DO NOT START ANOTHER GARMENT WITH LEFT-OVER YARN.  PLEAGE RETURN ALL UNUSED YARN TO CHAPTER	ron an  f swiit ao
Neck should measure at least 22-23 inches around when s  Sew up side and armhole seams, using an overcast stit  Press body of sweater (BUT NOT THE RIBEING) with warm i damp cloth.  CHAPTER LABEL should be sewed inside the back at neck o  SIZE OF SWEATER should be indicated either on Chapter 1 on a separate tag.  DO NOT START ANOTHER GARMENT WITH LEFT-OVER YARN.  PLEASE RETURN ALL UNUSED YARN TO CHAPTER	ron an  f swiit ao
Neck should measure at least 22-23 inches around when s  Sew up side and armhole seams, using an overcast stit  Press body of sweater (BUT NOT THE RIBETING) with warm i damp cloth.  CHAPTER LABEL should be sewed inside the back at neck o  SIZE OF SWEATER should be indicated either on Chapter 1 on a separate tag.  DO NOT START ANOTHER GARMENT WITH LEFT-OVER YARN.  PLEASE RETURN ALL UNUSED YARN TO CHAPTER  THE AMERICAN NATIONAL RED CROSS	ron an  f swiit ao
Neck should measure at least 22-23 inches around when s  Sew up side and armhole seams, using an overcast stit  Press body of sweater (BUT NOT THE RIBEING) with warm i damp cloth.  CHAPTER LABEL should be sewed inside the back at neck o  SIZE OF SWEATER should be indicated either on Chapter 1 on a separate tag.  DO NOT START ANOTHER GARMENT WITH LEFT-OVER YARN.  PLEASE RETURN ALL UNUSED YARN TO CHAPTER  THE AMERICAN NATIONAL RED CROSS  WASHINGTON, D. C.	ron an  f swiit ao
Neck should measure at least 22-23 inches around when s  Sew up side and armhole seams, using an overcast stit  Press body of sweater (BUT NOT THE RIBETING) with warm i damp cloth.  CHAPTER LABEL should be sewed inside the back at neck o  SIZE OF SWEATER should be indicated either on Chapter 1 on a separate tag.  DO NOT START ANOTHER GARMENT WITH LEFT-OVER YARN.  PLEASE RETURN ALL UNUSED YARN TO CHAPTER  THE AMERICAN NATIONAL RED CROSS	ron an  f swiit ao
Neck should measure at least 22-23 inches around when s  Sew up side and armhole seams, using an overcast stit  Press body of sweater (BUT NOT THE RIBEING) with warm i damp cloth.  CHAPTER LABEL should be sewed inside the back at neck o  SIZE OF SWEATER should be indicated either on Chapter 1 on a separate tag.  DO NOT START ANOTHER GARMENT WITH LEFT-OVER YARN.  PLEASE RETURN ALL UNUSED YARN TO CHAPTER  THE AMERICAN NATIONAL RED CROSS  WASHINGTON, D. C.	ron an  f swiit ao
Neck should measure at least 22-23 inches around when s  Sew up side and armhole seams, using an overcast stit  Press body of sweater (BUT NOT THE RIBEING) with warm i damp cloth.  CHAPTER LABEL should be sewed inside the back at neck o  SIZE OF SWEATER should be indicated either on Chapter 1 on a separate tag.  DO NOT START ANOTHER GARMENT WITH LEFT-OVER YARN.  PLEASE RETURN ALL UNUSED YARN TO CHAPTER  THE AMERICAN NATIONAL RED CROSS  WASHINGTON, D. C.	ron an  f swiit ao
Neck should measure at least 22-23 inches around when s  Sew up side and armhole seams, using an overcast stit  Press body of sweater (BUT NOT THE RIBEING) with warm i damp cloth.  CHAPTER LABEL should be sewed inside the back at neck o  SIZE OF SWEATER should be indicated either on Chapter 1 on a separate tag.  DO NOT START ANOTHER GARMENT WITH LEFT-OVER YARN.  PLEASE RETURN ALL UNUSED YARN TO CHAPTER  THE AMERICAN NATIONAL RED CROSS  WASHINGTON, D. C.	ron an  f swiit e?  abel &
Neck should measure at least 22-23 inches around when s  Sew up side and armhole seams, using an overcast stit  Press body of sweater (BUT NOT THE RIBEING) with warm i damp cloth.  CHAPTER LABEL should be sewed inside the back at neck o  SIZE OF SWEATER should be indicated either on Chapter 1 on a separate tag.  DO NOT START ANOTHER GARMENT WITH LEFT-OVER YARN.  PLEASE RETURN ALL UNUSED YARN TO CHAPTER  THE AMERICAN NATIONAL RED CROSS  WASHINGTON, D. C.	ron an  f swiit a?  abel &
Neck should measure at least 22-23 inches around when s  Sew up side and armhole seams, using an overcast stit  Press body of sweater (BUT NOT THE RIBEING) with warm i damp cloth.  CHAPTER LABEL should be sewed inside the back at neck o  SIZE OF SWEATER should be indicated either on Chapter 1 on a separate tag.  DO NOT START ANOTHER GARMENT WITH LEFT-OVER YARN.  PLEASE RETURN ALL UNUSED YARN TO CHAPTER  THE AMERICAN NATIONAL RED CROSS  WASHINGTON, D. C.	ron an  f swiit e?  abel &
Neck should measure at least 22-23 inches around when s  Sew up side and armhole seams, using an overcast stit  Press body of sweater (BUT NOT THE RIBEING) with warm i damp cloth.  CHAPTER LABEL should be sewed inside the back at neck o  SIZE OF SWEATER should be indicated either on Chapter 1 on a separate tag.  DO NOT START ANOTHER GARMENT WITH LEFT-OVER YARN.  PLEASE RETURN ALL UNUSED YARN TO CHAPTER  THE AMERICAN NATIONAL RED CROSS  WASHINGTON, D. C.	ron an  f swiit e?  abel &
Nock should measure at least 22-23 inches around when s  Sew up side and armhole seams, using an overcast stit  Press body of sweater (BUT NOT THE RIBEING) with warm i damp cloth.  CHAPTER LABEL should be sewed inside the back at neck o  SIZE OF SWEATER should be indicated either on Chapter 1 on a separate tag.  DO NOT START ANOTHER GARMENT WITH LEFT-OVER YARN.  PLEAGE RETURN ALL UNUSED YARN TO CHAPTER  THE AMERICAN NATIONAL RED CROSS  WASHINGTON, D. C.	ron an  f swii e?  abel &
Neck should measure at least 22-23 inches around when s  Sew up side and armhole seams, using an overcast stit  Press body of sweater (BUT NOT THE RIBEING) with warm i damp cloth.  CHAPTER LABEL should be sewed inside the back at neck o  SIZE OF SWEATER should be indicated either on Chapter 1 on a separate tag.  DO NOT START ANOTHER GARMENT WITH LEFT-OVER YARN.  PLEASE RETURN ALL UNUSED YARN TO CHAPTER  THE AMERICAN NATIONAL RED CROSS  WASHINGTON, D. C.	ron an  f swiit e?  abel &
Nock should measure at least 22-23 inches around when s  Sew up side and armhole seams, using an overcast stit  Press body of sweater (BUT NOT THE RIBETING) with warm i damp cloth.  CHAPTER LABEL should be sewed inside the back at neck o  SIZE OF SWEATER should be indicated either on Chapter 1 on a separate tag.  DO NOT START ANOTHER GARMENT WITH LEFT-OVER YARN.  PLEASE RETURN ALL UNUSED YARN TO CHAPTER  THE AMERICAN NATIONAL RED CROSS  WASHINGTON, D. C.	ron an  f swiit a?  abel &
Nock should measure at least 22-23 inches around when s  Sew up side and armhole seams, using an overcast stit  Press body of sweater (BUT NOT THE RIBETING) with warm i damp cloth.  CHAPTER LABEL should be sewed inside the back at neck o  SIZE OF SWEATER should be indicated either on Chapter 1 on a separate tag.  DO NOT START ANOTHER GARMENT WITH LEFT-OVER YARN.  PLEASE RETURN ALL UNUSED YARN TO CHAPTER  THE AMERICAN NATIONAL RED CROSS  WASHINGTON, D. C.	ron an  f swii e?  abel &
Nock should measure at least 22-23 inches around when s  Sew up side and armhole seams, using an overcast stit  Press body of sweater (BUT NOT THE RIBETNG) with warm i damp cloth.  CHAPTER LABEL should be sewed inside the back at neck o  SIZE OF SWEATER should be indicated either on Chapter 1 on a separate tag.  DO NOT START ANOTHER GARMENT WITH LEFT-OVER YARN.  PLEASE RETURN ALL UNUSED YARN TO CHAPTER  THE AMERICAN NATIONAL RED CROSS  WASHINGTON, D. C.	ron an  f swiic e?  abel &
Nock should measure at least 22-23 inches around when s  Sew up side and armhole seams, using an overcast stit  Press body of sweater (BUT NOT THE RIBEING) with warm i damp cloth.  CHAPTER LABEL should be sewed inside the back at neck o  SIZE OF SWEATER should be indicated either on Chapter 1 on a separate tag.  DO NOT START ANOTHER GARMENT WITH LEFT-OVER YARN.  PLEASE RETURN ALL UNUSED YARN TO CHAPTER  THE AMERICAN NATIONAL RED CROSS  WASHINGTON, D. C.	ron an  f swii e?  abel &
Nock should measure at least 22-23 inches around when s  Sew up side and armhole seams, using an overcast stit  Press body of sweater (BUT NOT THE RIBEING) with warm i damp cloth.  CHAPTER LABEL should be sewed inside the back at neck o  SIZE OF SWEATER should be indicated either on Chapter 1 on a separate tag.  DO NOT START ANOTHER GARMENT WITH LEFT-OVER YARN.  PLEASE RETURN ALL UNUSED YARN TO CHAPTER  THE AMERICAN NATIONAL RED CROSS  WASHINGTON, D. C.	ron an  f swii e?  abel &